



RECESSED 3W GROUND RECESSED LUMINAIRE

- » dimmable, high-quality LED recessed in-ground luminaire for outdoor use
 - » milled aluminium housing, anodised - with either 304 or 316L stainless steel shield
 - » useable for light accentuation or as positioning light
 - » available as CV version in the color temperatures 2700 K, 3000 K and 4000 K plus four optional beam angles
 - » available as CC version for RGB and RGBW applications
 - » with integrated membrane for prevention of condensation and contamination through pressure compensation » incl. 5 m connection cable with free wire ends
 - » CV version optional fitting with M8 or M12 connector »
- estimated lifetime L70 at Ta < 45 °C: > 51,400 h
(> 60,000 h RGB(W))

RECESSED 3W 12/24V

SHIELD / MOUNTING: Ø 54,5 mm / Ø 40 mm



Item no.	Light color	Typ. color temp.	Typ. power	Typ. light output	Lumen/Watt	Typ. CRI	Beam angle
811	827 warm white	2700 K		220 lm	85 lm/W	83	
311	830 white	3000 K	2,6 W	230 lm	88 lm/W	83	12°
611	840 cool white	4000 K		240 lm	92 lm/W	83	
820	827 warm white	2700 K		220 lm	85 lm/W	83	
320	830 white	3000 K	2,6 W	230 lm	88 lm/W	83	21°
620	840 cool white	4000 K		240 lm	92 lm/W	83	
832	827 warm white	2700 K		220 lm	85 lm/W	83	
332	830 white	3000 K	2,6 W	230 lm	88 lm/W	83	34°
632	840 cool white	4000 K		240 lm	92 lm/W	83	
847	827 warm white	2700 K		220 lm	85 lm/W	83	
347	830 white	3000 K	2,6 W	230 lm	88 lm/W	83	44° x 9°
647	840 cool white	4000 K		240 lm	92 lm/W	83	

= 3 = shield: 304 stainless steel || # = 4 = shield: 316L stainless steel, brushed

RECESSED 3W SHIELD / MOUNTING: Ø 54,5 mm / Ø 40 mm



Item no.	Light color	Typ. color temp.	Max. power	Typ. light output	Lumen/Watt	Beam angle	EEK EEC
125	RGB	RGB	3 W	145 lm	48 lm/W	25°	A+
625	RGBW	RGBW	4,1 W	225 lm	55 lm/W	25°	A+

= 2 = shield: 304 stainless steel || # = 4 = shield: 316L stainless steel, brushed

SUITABLE ACCESSORIES

Item no.	Description
0121	ground mounting sleeve, aluminum, Ø 45 mm, length 120 mm

